

K200 Series 2 3/8" Frame Depth Horizontal Slider

K200 SERIES HORIZONTAL SLIDER

FEATURES

- ◇ Commercial Framing System
 - 2 3/8" main frame
 - 0.062" wall thickness of frame and sash
- ◇ Thermally Enhanced Design
 - Azon pour and debridge thermal break is 1/2" wide in all main frame and vent rail extrusions
 - Frame and sash mortised and joined with screw fasteners
 - Positive interlocks
 - Full length pull rail
- ◇ Glazing
 - 3/4" insulated glass
- ◇ Hardware
 - Brass rollers with stainless steel axle pins for easy operation
 - Sweep lock
- ◇ Screen
 - Extruded aluminum screen frame with BetterVue™ mesh with WaterShed® technology

BENEFITS

- ◇ The capacity to match exterior colors for unique project facades
- ◇ The ability to facilitate large sizes for taller and wider window openings

PERFORMANCE

- ◇ Structural & Thermal (test reports or thermal simulations available upon request)

Model	Horizontal Slider
AAMA/WDMA/CSA 101/I.S.2/A440-08 Rating	CW-PG40
Structural Load P.S.F.	60.15
Air at 50 MPH (cfm/ft ²)	<0.30
Water (No Penetration) P.S.F.	6.06
U-Value (with Low-E and Argon)	0.37 - 0.48
SHGC (with Low-E and Argon)	0.14 - 0.51

Window test size: 72" x 60"

Operating Force: 16 lbf (maintain motion), 3 lbf (locks)

OPTIONS

- ◇ Available Configurations
 - Fixed-Active
 - Active-Fixed
 - Active-Fixed-Active
 - Fixed-Active-Fixed
- ◇ Muntin Choices
 - Internal or simulated divided lites available
- ◇ Limited Travel Latch
- ◇ Nailing Fin
- ◇ Screen
 - Extruded aluminum screen frame with aluminum wire mesh
 - Extruded aluminum screen frame with sunscreen mesh
 - Extruded aluminum screen frame with stainless steel 0.009" thickness mesh
 - Security screen (limitations apply)
- ◇ Glazing
 - Multiple Low-E + argon glazing choices
 - Capillary tubes
 - Wide variety of glazing, tinting and thickness options
- ◇ Panning & Trim Choices
 - Wide variety of panning, receptor and trim available
- ◇ Mulling
 - Wide variety of structural mulls
- ◇ Specialty
 - Extension jambs
 - Louver




Our products are tested to the standards of and certified by some of the foremost organizations in the fenestration industry.






K200 SLIDER WITH NAILING FIN


This document contains confidential and proprietary information intended for the private use of Quaker.
© 2016 Quaker Window Products Co., INC. All rights reserved.
Quaker reserves the right to change any/all designs without notice.
Due to periodic re-certification requirements, result shown may vary.



(A) VERTICAL CROSS SECTION (B) VERTICAL CROSS SECTION



ELEVATION SCALE 1" = 1'-0"




SCALE 1:3




K200 SLIDER WITHOUT NAILING FIN

This document contains confidential and proprietary information intended for the private use of Quaker.
© 2016 Quaker Window Products Co., INC. All rights reserved.
Quaker reserves the right to change any/all designs without notice. Due to periodic re-certification requirements, result shown may vary.





① HORIZONTAL
CROSS SECTION




ELEVATION SCALE 1" = 1'-0"

Ⓐ VERTICAL
CROSS SECTION

Ⓑ VERTICAL
CROSS SECTION




SCALE 1:3




K200 CENTER VENT SLIDER

This document contains confidential and proprietary information intended for the private use of Quaker.
© 2016 Quaker Window Products Co., INC. All rights reserved.
Quaker reserves the right to change any/all designs without notice.
Due to periodic re-certification requirements, result shown may vary.




① HORIZONTAL CROSS SECTION



① A VERTICAL CROSS SECTION

① B VERTICAL CROSS SECTION



SCALE 1:3

