

Casement | Project-Out | Fixed



Product Material Aluminum



Frame Depth **3** ½¹/4



Rating
Casement: Up to CW90
Project-Out: Up to CW90
Fixed: Up to AW110



Design Pressure Casement: Up to 90 Project-Out: Up to 90 Fixed: Up to 110	U-Value* Casement: .3944 Project-Out: .4060 Fixed: .2531
Air Infiltration Casement: <.30 Project-Out: <.30 Fixed: <.10	SHGC* Casement: .1448 Project-Out: .1448 Fixed: .1657
Water Resistance Casement: Up to 12 Project-Out: Up to 12 Fixed: Up to 15	* CR* Casement: 45 - 48 Project-Out: 40 - 49 Fixed: 49 - 62
OITC [×])))) Casement: 29 - 32 Other models: Contact Quaker	STC ^X)))) Casement: 34 - 37 Other models: Contact Quaker

- *-Ranges based on multiple Low-E/Argon I.G. combinations
- ^x-Ranges based on multiple I.G. combinations

FEATURES:


- ► Historically-correct bevel frame
- Casement and Project-out operating models
- ► Architectural grade aluminum frame
- ► Thermally-broken frame and sash with pourand-debridge technology
- ▶ 2⁷/₁₆" narrow sitelines
- ▶ With or without Integral Nailing Fin
- ► 1" insulating glass
- ► Standard High-Performance 2604 Powder Paint Finish (an FGIA Specification)
- Optional upgrade to 2605 Powder Paint Finish (an FGIA Specification)
- ➤ 30+ "Quick-Pick" colors, with unlimited custom colors available.
- Optional Upgrade to 2605 Powder Paint Finish (an FGIA Specification)
- ► Impact rated versions (H470 Series): Project-Out model w/cam handle and Fixed model



H450 HISTORICAL ALUMINUM SERIES


Casement Roto (CW90)

Test size = 36" x 60"




Casement Push/Pull Cup (CW90)

Test size = 36" x 60"




Fixed (AW110/AW60)

AW110 Test size = 72" x 110" AW60 Test Size = 60" x 99"




Project-Out Roto (CW90)

Test size = 60" x 36"



Project-Out Push/Pull Cup (CW90)

Test size = 60" x 36"



All ratings listed are NAFS certified.





QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com