





Project-Out: 70 Project In: 70 Fixed: 70	Casement: .4146 Project-Out: .4146 Project In: .4347 Fixed: .2734
Air Infiltration	SHGC*
Casement: <.10	Casement: .1241
Project-Out: <.10	Project-Out: .1241
Project In: <.10	Project In: .1241
Fixed: <.10	Fixed: .1555
Water Resistance	* CR*
Casement: 12	Casement: 42 - 46
Project-Out: 12	Project-Out: 43 - 47
Project In: 12	Project In: 43 - 44
Fixed: 12	Fixed: 46 - 55
OITC [×]	STC [×]
))) All models: Contact))) All models: Contact
Quaker	Quaker

^x-Ranges based on multiple I.G. combinations

FEATURES:

- Architectural grade aluminum frame
- Thermally-broken with pour-and-debridge technology
- ▶ 1" insulating glass
- Casement, Project-Out and Project-In operating models
- Matching Fixed model
- Heavy commercial hardware on all operating models
- Casement hinging allows for 90° opening for full ventilation capabilities
- ► 30+ "Quick-Pick" colors, with unlimited custom colors available
- Standard High-Performance 2604 Powder Paint Finish (an FGIA Specification)
- Optional Upgrade to 2605 Powder Paint Finish (an FGIA Specification)


www.QuakerCommercialWindows.com

Information listed is deemed accurate as of date shown. Quaker Windows reserves the right to change or discontinue any product, feature or option without notice.




T600 ALUMINUM SERIES

Casement Roto (AW70)



Project-Out Roto (AW70) Test size = 60" x 36"




Casement Cam Handle (AW70)

WINDOW HEIGHT


36

Test size = 36" x 60"

Casement Project In (AW70)




Fixed (AW70) Test size = 72" x 120"





QuakerCommercialWindows.com 1-800-347-0438

Commercial@quakerwindows.com



Project-Out Cam Handle (AW70)

All ratings listed are NAFS certified.